

Bar Code Advertising Displayer

FV FlashView 3400 Series
Control Your Message



industrial
image inc.

www.industrialimage.net
866-905-6400
sales@industrialimage.net

Main Feature:

Easy to use file renaming method for bar code detection. Simply rename each file name with its bar code number and the device will play its content when the bar code is detected.

Other Features:

USB updates:
Auto file update through USB thumb drive

Access Controls:
Remote control device or manual control at top of device.

Enclosure:
Metal housing available in black and silver protected with Anti-Glare tempered glass

Storage Medium:
Compact Flash memory card

OSD Languages:
English, Francais, Deutsch, Italiano, Swedish, Danish, Portuguese, Spanish

Playback modes:
Auto start, play, repeat and slideshow

Certification:
CE, FCC, RoHS

industrial
image inc. **THE STANDALONE**
Digital Signage Source

Bar Code Advertising Displayer

FV FlashView 3400 Series Control Your Message

Technical Specification:

Available LCD size	7", 10.2", 15", 17", 19", 32"
Memory card Supported	Compact Flash Card Type I/II, USB 2.0
File Format Supported	Jpeg, Mpeg 1,2,3 and 4
Input Voltage	100 to 240 V, AC 50/60 Hz
Operating Temperature	10°C to 70°C
Indicator (LED)	Dual Color (on/off state)
Cell type	TFT
Input	VGA, AV, 3.5mm Stereo In
Input voltage	AC 100-240V, 50/60Hz

Scanner Specification

Light Source	650nm visible laser diode
Depth of Scan Field	20 - 200mm
Number of Scan Lines	20
Scan Pattern	5 direction of scan field
Scan Speed	
Minimum Bar Width	5mil at PCS 90%
Print Contrast	30% at UPC/EAN 100%
Indicators (LED)	Two-color (green & red)
Beeper Operation	Programmable tone and beep time
System Interfaces	Keyboardm RS-232C, USB, Wand
Laser Class	CDRH Class II a: IEC 60825-1, Class 1
EMC	CE & FCC DOC compliance
Operating Temperature	0-40°C
Light Levels	Max. 2500 LUX (fluorescence)



www.industrialimage.net
866-905-6400
sales@industrialimage.net



THE STANDALONE
Digital Signage Source