

Sunlight Readable LCD



Sunlight Readable LCD

15"

Specifications

Model Name	OF153-600T
Viewable Size Image	15"
Active Display Area(mm)	204.128(H)x228.096(V)
Pixel Pitch(mm)	0.297(H)x0.297(V)
Number of Pixels	1024x768
Contrast Ratio	400:1(typ.)
Display Color	262144(6bit/colors)
Brightness(cd/m ²)	600
Viewing Angle(CR>=10)	-70~70(H);-60~60(V)
Synchronization Range	31.5~60.0KHz/60~75Hz
Horizontal/Vertical	
Recommended Resolution	1024x768@60Hz,75Hz
Signal Connector	15 pin D-Sub
Power Source	AC100~240V, Universal, 10%
Power Consumption	35W typical, normal operation
Power Management	VESA DPMS Compliant
Plug & Play	VESA DDC 1/2B
Optional Video Input	S-Video, Composite
Optional DVI Input	No
Optional Touch Screen	IR,SAW
Optional protection glass(reflection rate<0.5%)	UV glass / clear type glass

Outdoor readability

Ambient light(nit)	Brightness measure Angle	10,000	30,000	80,000
Brightness gain(BL0n)(nit)	35°	600	780	1,150
Reflectance(net)(%)		1%	0.98%	0.9%

Remarks:OF153-600T= VGAInput only

OF153-600TV series= VGA+VideoInput



Industrial Image, Inc.
2665 Pine Grove Rd. Ste 400
Cumming, GA 30041
PH: 770-205-6636 FAX: 770-205-6858

Mechanical Drawing

