

Open Frame LCD



8"

Specifications

RoHS
COMPLIANT
2002/95/EC

| | |
|--------------------------------|-------------------------------|
| Model Name | OF8X1-350 |
| Viewable Size Image | 8" |
| Active Display Area(mm) | 162.2(H)x121.7(V) |
| Pixel Pitch(mm) | 0.2535(H)x0.2535(V)(typ.) |
| Number of Pixels | 640x480 |
| Contrast Ratio | 250:1 (typ.) |
| Brightness(cd/m ²) | 350 |
| Viewing Angle(CR>=10) | -65~65(H);-65~50(V) |
| Synchronization Range | 31.5~37.5KHz/60~75Hz |
| Horizontal/Vertical | |
| Recommended Resolution | 640x480@60Hz,75Hz |
| Signal Connector | 15 pin D-Sub |
| Power Source | AC100~240V, Universal, ±10% |
| Power Consumption | 20W typical, normal operation |
| Power Management | VESA DPMS Compliant |
| Plug & Play | VESA DDC 1/2B |
| Optional Video Input | S-Video, Composite |
| Optional DVI Input | No |
| Optional Touch Screen | No |

Remarks:OF8X1-350 series= VGA input only
OF8X1-350V series= VGA+Video Input

Mechanical Drawing

