

# OFV153-250

## 15" Open Frame LCD Monitor

### Benefits and Advantages

- Industrial grade-A LCD TFT active-matrix color panel
- EMI shielding around the monitor housing to minimize interference
- Easy to integrate into a variety of enclosures
- Installs quickly and easily with plug and play system configuration
- Durable construction for kiosk, retail, hospitality, and gaming applications
- Product life cycle is three years minimum



### Specifications

Model Name	OFV153-250
Viewable Size Image	15"
Active Display Area(mm)	304.128(H)x228.096(V)
Pixel Pitch(mm)	0.297(H)x0.297(V)
Number of Pixels	1024x768
Contrast Ratio	400:1(typ.)
Display Color	16.7M(8bits/colors)
Brightness(cd/m) <sup>2</sup>	250(typ.)
Viewing Angle(CR>=10)	-89~89(H); -89~89(V)
Synchronization Range	31.5~60.0KHz/56~75Hz
Horizontal/Vertical	
Recommended Resolution	1024x768@60Hz,75Hz
Signal Connector	15 pin D-Sub
Power Source	AC100~240V, Universal, ±10%
Power Consumption	15W typical, normal operation
Power Management	VESA DPMS Compliant
Plug & Play	VESA DDC 1/2B
Optional Video Input	Composite, S-Video
Optional DVI Input	Yes
Optional Touch Screen	Resistive, Capacitive, SAW, IR

Model Options: OFV153-250 series= VGA Input only  
 OFV153-250V Series= VGA+Video Input

